THE **VEHICLE**

THE **SATELLITE**

PROTON HISTORY

Lead designer was Vladimir Chelomei, who designed it with the intention of creating both a powerful rocket for military payloads and a high-performance ICBM. The program was changed, and the rocket was developed exclusively for launching spacecraft.

First named UR-500, but adopted the name "Proton," which also was the name of the first three payloads launched.

Proton launched Russian interplanetary missions to the Moon, Venus, Mars, and Halley's Comet.

Proton launched the Salyut space stations, the Mir core segment and both the Zarya (Dawn) and Zvezda (Star) modules for today's International Space Station.

First commercial Proton launch — 9 April 1996.

First commercial Proton M Breeze M launch
 — 30 December 2002

P

0





GROSS LIFT-OFF WEIGHT 705.000 kg

705,000 kg (1,554,000 lb)

PROPELLANT UDMH and NTO

INITIAL LAUNCH 16 July 1965 Proton-1 Spacecraft

Payload Fairings

There are multiple payload fairing designs presently qualified for flight, including standard commercial payload fairings developed specifically to meet the needs of our customers.

Breeze M Upper Stage

The Breeze M is powered by one pump-fed gimbaled main engine that develops thrust of 20 kN (4,500 lbf). It is composed of a central core and an auxilliary propellant tank which is jettisoned in flight following depletion. The Breeze M control system includes an on-board computer, a three-axis gyro stabilized platform, and a navigation system. The quantity of propellant carried is dependent on specific mission requirements and is varied to maximize mission performance.

PROTON BOOSTER

The Proton booster is 4.1 m (13.5 ft) in diameter along its second and third stages, with a first stage diameter of 7.4 m (24.3 ft). Overall height of the three stages of the Proton booster is 42.3 m (138.8 ft).

THIRD STAGE

Powered by one RD-0213 engine, this stage develops thrust of 583 kN (131,000 lbf), and a four-nozzle vernier engine that produces thrust of 31 kN (7,000 lbf). Guidance, navigation, and control of the Proton M during operation of the first three stages is carried out by a triple redundant closed-loop digital avionics system mounted in the Proton's third stage.

SECOND STAGE

Of conventional cylindrical design, this stage is powered by three RD-0210 engines plus one RD-0211 engine and develops a vacuum thrust of 2.4 MN (540,000 lbf).

FIRST STAGE

The first stage consists of a central tank containing the oxidizer surrounded by six outboard fuel tanks. Each fuel tank also carries one of the six RD-276 engines that provide first stage power. Total first stage vacuum-rated level thrust is 11.0 MN (2,500,000 lbf).

The Proton and the Breeze M are built by Khrunichev State Research and Production Space Center.



SATELLITE OPERATOR

SES www.ses.com

SATELLITE MANUFACTURER

EADS Astrium www.astrium.eads.net.com

PLATFORM

E3000

SEPARATED MASS

6100 kg

SATELLITE MISSION LIFETIME

15 Years

SATELLITE MISSION

SES-6 is a multipurpose satellite built by EADS Astrium and will be replacing NSS-806 at 319.5° east to provide significant capacity expansion over North America, Latin America and the Caribbean, Europe, and Atlantic Ocean region. The satellite's expanded Ku-band payload will support DTH platforms, VSAT services and government digital inclusion programs throughout Latin America. The C-band payload will add incremental capacity to support channel growth at this key cable neighborhood.



Mission Overview



Experience ILS: Achieve Your Mission

QUALITY | PERFORMANCE | EXPERIENCE | DEDICATION



www.ilslaunch.com

SES-6

- 4th ILS Proton Launch in 2013
- 81st ILS Proton Launch Overall
- 22nd SES Satellite Launched on ILS Proton
- 16th EADS Astrium Satellite Launched on Proton
- 2nd Commercial SSTO Mission

THE MISSION

Ignition

04:23:49

3rd Burn = 09:26

Shutdown

04:33:15

APT Jettison

04:34:05


2nd Burn = 19:34

Shutdown

02:10:04

Ignition

01:50:30



MISSION DESCRIPTION

1st Burn = 04:27

Shutdown

00:15:43

Ignition

00:11:16

The Proton M launch vehicle, utilizing a 5-burn Breeze M mission design, will liftoff from Pad 39 at Baikonur Cosmodrome, Kazakhstan, with the SES-6 satellite on board. The first three stages of the Proton will use a standard ascent profile to place the orbital unit (Breeze M Upper Stage and the SES-6 satellite) into a sub-orbital trajectory. From this point in the mission, the Breeze M will perform planned mission maneuvers to advance the orbital unit first to a circular parking orbit, then to an intermediate orbit, followed by a transfer orbit, and finally to a super-synchronous transfer orbit. Separation of the SES-6 satellite is scheduled to occur approximately 15 hours, 31 minutes after liftoff.



GROUND TRACK

Shutdown

04:43:57

5th Burn = 03:34

Shutdown

15:18:39

Ignition

15:15:05

Spacecraft

Separation

15:31:00

4th Burn = 08:25

Ignition

04:35:32

